

November 6, 2009

ADDENDUM #1 TO  
MONTANA DEPARTMENT OF TRANSPORTATION  
INVITATION FOR BID  
#HWY-309379-RP

The purpose of this addendum is for the clarification on the Wheelchair Lift and Restraint Track for the 12&13-Passenger Cutaway Transit Minibuses.

Change Section 3.9, Wheelchair Lift and Restraint Devices, item #12, Wheelchair Restraint Track to read as follows:

12.	<p><u>Wheelchair Restraint Track</u> For vehicles with a front wheelchair lift:</p> <ul style="list-style-type: none"><li>a) Four (4) pieces of “L” track shall be mounted on the floor, curbside behind the driver’s area modesty panel and <b>run continuously</b> to the first row of passenger seats</li><li>b) One (1) piece of “L” track shall be mounted on the wall, above the curbside windows, behind the driver’s area modesty panel and <b>run continuously</b> to the first row of passenger seats</li></ul> <p>For vehicles with a rear wheelchair lift:</p> <ul style="list-style-type: none"><li>a) Two (2) pieces of “L” track shall be mounted on the floor behind last row of passenger seats and <b>run continuously</b> from the street side to the curbside of the vehicle</li><li>b) Two (2) pieces of “L” track shall be mounted on the floor adjacent to the rear wall and <b>run continuously</b> from the street side to the curbside of the vehicle</li><li>c) One (1) piece of “L” track shall be mounted on either side of the rear emergency door. Track length shall be a minimum of six (6) inches. See following picture for guidance:</li></ul>	12.	<ul style="list-style-type: none"><li>a)</li><li>b)</li><li>a)</li><li>b)</li><li>c)</li></ul>
-----	--	-----	--



<ul style="list-style-type: none"> <li>- Wall mounted track shall be used for the shoulder harness / lap belt restraint</li> <li>- <b>All track must be Sure-Lok "L" Fitting Series or approved equal</b></li> <li>- All track must be mounted flush with the surface material</li> <li>- Each vehicle shall have a total of two (2) wheelchair placement stations. Each station shall have tie down locations for four (4) wheelchair restrains and one (1) shoulder harness / lap belt restraint</li> <li>- All track must meet ADA wheelchair placement requirements</li> </ul>	List Type of Track: _____ Brand _____ Model _____
--	--

All other terms, conditions, specifications and incidentals shall remain the same as originally stated in Invitation for Bid #HWY-309379-RP

**ADDENDUM ACKNOWLEDGEMENT:**

\_\_\_\_\_ (Vendor Signature)

\_\_\_\_\_ (Date)

hereby acknowledge that I have received a copy of Addendum #1.

A copy of this signed addendum **MUST** be included with your bid response. Failure to include a copy of this addendum with your response will result in disqualification of your response.

MDT attempts to provide accommodations for any known disability that may interfere with a person participating in any service, program or activity of the Department. Alternative accessible formats of this information will be provided upon request. For further information call Richele Parkhurst at (406) 657-0274 Voice or 1-800-335-7592 TTY or TTY (406) 444-7696.